



## FEATURES

- 1+1 AUTOMATIC CHANGE OVER RF AND AUDIO
- CONTROL POWER FROM 100W TO 20KW
- COMPATIBLE WITH ALL RF COAXIAL SWITCH
- LARGE LCD COLOR DISPLAY WITH TOUCH PANEL
- WEB SERVER
- REMOTE CONTROL
- OPTION
- SNMP REMOTE CONTROL
- MOBILE REMOTE CONTROL

## TECHNICAL SPECIFICATIONS

### GENERAL

POWER CONTROL	100W-20KW ( WITH DIFFERENT RF COAXIAL SWITCH)
OPERATION	AUTOMATIC / MANUAL
CONTROL	LOCAL / REMOTE
SETTING TIME	5-60 SEC.
PRESET	
AUTOMATIC RESET	5-900 MIN.
EXTERNAL INTERLOCK	
COMPATIBLE WITH ALL RF COAXIAL SWITCH	

### AUDIO

LEFT & RIGHT INPUT	XLR CONNECTOR
2 LEFT & RIGHT OUTPUT	XLR CONNECTOR
4 COMPOSITE/SCA INPUT	BNC CONNECTOR
8 COMPOSITE/SCA INPUT	BNC CONNECTOR

### EXTERNAL CONNECTION

COAXIAL SWITCH	DB9 MALE
TX A	DB9 FEMALE
TX RESERVE	DB25 FEMALE
RS485	DB9 FEMALE
LAN	RJ45
TX A	DB9 FEMALE

### ELECTRICAL

AC Input Power	90÷260 VAC 50/60 HZ single phase
----------------	----------------------------------

### ENVIRONMENTAL

Operating temperature	-5°C to +50°C
Max Operating Altitude	5000 mt
Relative Humidity Range	0 to 90%

### PHYSICAL DIMENSION

Mounting	Standard 19" chassis 2 U rack
Size	W x 483 mm. D x 470 mm. H x 88 mm
Weight	~ 3,0 Kg.